



# LIGHT TRUCK TYRES



LIGHT TRUCK TYRES

# LIGHT TRUCK TYRES



## SUPERLUG



Features	Benefits
<ul style="list-style-type: none"> <li>• Unique tread compound</li> <li>• Special design with scoops at shoulder</li> <li>• Extra strong casing</li> <li>• Aggressive tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Cooler running</li> <li>• Excellent mileage</li> <li>• Better road grip</li> <li>• Better safety and more retreads</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	12	5.5F	205	775	16.0	1175@6.30	-	365	-	TR 15
7.00-16	14	5.5F	204	805	17.0	1315@6.90	1160@6.90	381	16M/16N	AB 1582
7.50-16	16	6.0G	212	825	18.0	1580@7.75	1390@7.75	388	16N	AB 1582
8.25-16	16	6.5	229	863	19.0	1845@ 6.70	1755@ 6.70	406	16N	TR 177A

## SUPER TRACTION



Features	Benefits
<ul style="list-style-type: none"> <li>• Aggressive tread pattern</li> <li>• Strong casing</li> </ul>	<ul style="list-style-type: none"> <li>• Superior traction</li> <li>• High road contact area enhancing road grip</li> <li>• Designed for all wheel fitment</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	8	5.5F	196	760	15.3	925@4.20	816@4.20	369	-	TR 75A
7.00-16	8	5.5F	198	785	15.3	966@4.20	840@4.20	372	16N	AB 1582
7.00-16	10	5.5F	198	785	15.3	1090@5.25	975@5.25	372	16N	AB 1582
7.50-16	8	6.0G	210	810	15.0	1105@4.25	970@4.25	382	16N	AB 1582
7.50-16	12	6.0G	210	810	15.0	1405@6.30	1240@6.30	382	16N	AB 1582

# LIGHT TRUCK TYRES



## M - 77



Features	Benefits
<ul style="list-style-type: none"> <li>• Rib lug tread pattern</li> <li>• Aggressive tread design</li> </ul>	<ul style="list-style-type: none"> <li>• All wheel fitment</li> <li>• Better mileage</li> <li>• Excellent traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	10	5.5F	205	780	15.2	1050@5.25	925@5.25	367	-	TR 15
7.00-15	12	5.5F	205	780	15.2	1175@6.30	1030@6.30	367	-	TR 15
7.50-16	14	6.0G	213	827	18.0	1495@7.05	1315@7.05	391	16N	AB1582

## SUPERMILER



Features	Benefits
<ul style="list-style-type: none"> <li>• 5 rib design pattern</li> <li>• Unique fan like shoulder design</li> </ul>	<ul style="list-style-type: none"> <li>• Good mileage and traction</li> <li>• Better retreadability</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT215/80D14	10	5.5J	211	691	11.0	1125@5.25	-	324	-	TR 13
LT215/80D14	10	5.5J	211	691	11.0	1125@5.25	-	324	-	TUBELESS
6.70-15	8	5.0K	180	718	12.0	820@4.25	-	335	-	TR 15
7.00-15	8	5.5F	200	772	12.5	925@4.25	-	363	-	TR 15
7.00-15	10	5.5F	200	772	12.5	1050@5.25	-	363	-	TR 15
6.50-16	8	4.5F	174	753	12.5	860@4.25	-	355	-	TR 15
7.00-16	10	5.5F	204	797	12.5	1100@5.25	965@5.25	372	16N	AB1582
7.00-16	12	5.5F	204	797	12.5	1215@6.20	1065@6.20	378	16N	AB1582
7.50-16	12	6.0G	207	810	13.0	1405@6.30	1240@6.30	382	16N	AB1582
7.50-16	14	6.0G	207	810	13.0	1495@7.05	1315@7.05	382	16N	AB1582
8.25-16	16	6.5	229	854	14.0	1845@ 6.70	1755@ 6.70	402	16N	TR 177A



## HIGHWAY



Features	Benefits
<ul style="list-style-type: none"> <li>• Unique rib tread pattern</li> <li>• Free rolling tread design</li> <li>• Cooler running compound</li> </ul>	<ul style="list-style-type: none"> <li>• Good road grip</li> <li>• Good mileage</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	8	5.5F	200	757	11.2	925@4.20	815@4.20	367	-	TR 15
7.00-16	8	5.5F	200	783	11.2	965@4.20	850@4.20	371	16N	AB1582
7.50-16	8	6.0G	212	810	11.5	1105@4.25	970@4.25	382	16N	AB1582
7.50-16	12	6.0G	212	810	11.5	1405@6.30	1240@6.30	382	16N	AB1582
7.50-16	14	6.0G	215	824	11.5	1495@7.00	1315@7.00	387	16N	AB1582

## LCV RADIAL



## STEEL MUSCLE

Features	Benefits
<ul style="list-style-type: none"> <li>• 4 rib design</li> <li>• Unique tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Enhanced mileage and traction</li> <li>• Better road grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 7.00 R15	10	5.5	206	755	12.5	1050@5.60	-	350	-	TR 150



## STEEL MUSCLE - L



Features	Benefits
<ul style="list-style-type: none"> <li>• Specially designed tread block</li> <li>• Good retreadability</li> <li>• Specially designed tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Low heat generation</li> <li>• Excellent traction &amp; gripping</li> <li>• Long wear life</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 185 R 14	8	5.5J	189	654	10.5	850@4.6	800@4.6	302	-	TR 13
LT 7.00 R 16	10	5.5F	203	778	12.5	1100@5.6	965@5.6	362	16N	TR 15
LT 7.00 R 16	12	5.5	203	778	12.5	1215@6.7	1065@6.7	362	16N	TR 15
LT 7.50 R 16	14	6.0	212	814	12.5	1495@7.40	1315@7.40	375	16N	TR 15
LT185/85 R 16	8	6.0J	185	725	9.5	925@4.58	-	335	-	-

## STEEL MUSCLE - R



Features	Benefits
<ul style="list-style-type: none"> <li>• Exclusive highway application</li> <li>• Rib design for excellent resistance to uneven wear</li> </ul>	<ul style="list-style-type: none"> <li>• Good maneuverability</li> <li>• Excellent mileage</li> <li>• Good cornering control</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 185 R 14	8	5.5	189	654	10.5	850@4.6	800@4.6	302	-	TR 13
LT 7.00 R 16	10	5.5	203	778	12.5	1100@5.6	965@5.6	362	16N	TR 15
LT 7.00 R 16	12	5.5	203	778	12.5	1215@6.7	1065@6.7	362	16N	TR 15



## STEEL MUSCLE

Features	Benefits
<ul style="list-style-type: none"> <li>• 4 rib design</li> <li>• Unique tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Enhanced mileage and traction</li> <li>• Better road grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 7.50 R16	14	6.0	214	815	12.5	1495@7.40	1315@7.40	381	16N	AB1582
LT 7.50 R16	12	6.0	212	814	12.5	1405@6.70	1240@6.70	375	16N	TR 15



## ZQT

Features	Benefits
<ul style="list-style-type: none"> <li>• Specially designed tread pattern for even wear</li> <li>• Excellent all-season performance</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent mileage</li> <li>• Enhanced road grip</li> <li>• Smooth and quiet ride</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
195/70 R14	6	6.0J	196	632	10.5	690@2.96	-	292	-	-
235/70 R16	6	7J	236	733	10.3	925@2.45	-	328	-	-
215 R14	112/110P	6J	216	704	12.25	1120@4.6	160@4.6	324	-	-
235/75 R15	105Q	6.5J	235	733	10.75	925@2.45	-	328	-	-
265/70 R16	112Q	8J	272	778	10.75	1120@2.45	-	348	-	-

# LIGHT TRUCK TYRES



## ZGT



Features	Benefits
<ul style="list-style-type: none"> <li>• Futuristic design</li> <li>• Bold block tread pattern</li> <li>• Sporty looks</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent traction</li> <li>• Quick handling response</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 195 R 15	8	5.5K	197	697	10.5	950@4.6	-	321	-	TR 13

## ZGP



Features	Benefits
<ul style="list-style-type: none"> <li>• Bold block tread pattern</li> <li>• All terrain tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent even on rugged terrains</li> <li>• Enhanced breaking and stability</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 235/75 R15	6	6.5J	240	735	12.5	900@3.5	825@3.5	334	-	TR 13



## JOGGER - A/T



Features	Benefits
<ul style="list-style-type: none"> <li>• Bold aggressive pattern</li> <li>• Excellent traction</li> <li>• All terrain rugged design</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent ride control</li> <li>• Long life</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
6.50 R 16	8	4.5	185	750	10.5	920@4.85	870@4.85	339	-	-

## ZVTS



Features	Benefits
<ul style="list-style-type: none"> <li>• Carcass incorporates supple sidewalls</li> <li>• Deeper tread grooves in an optimised tread design</li> <li>• Tread design features higher sipe density and computerised tread pitch sequence</li> <li>• Premium all-season tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Supple sidewalls for comfort &amp; reliability</li> <li>• Outstanding traction and responsive braking capability</li> <li>• Optimum traction and a smooth, quiet ride</li> <li>• Special polymer compound provides long-term even tread wear</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 175 R 14	6	5J	180	635	9.5	710@3.86	670@3.86	280	-	-